

MASE0606021R5

EMC SINGLE DOOR ENCLOSURE



The galvanised steel single door wall mounted enclosure range, MASE, is designed to meet EMC requirements. An excellent Faraday effect is created, since electrical conductivity between the enclosure body and door is guaranteed. The risk for component failure, and with that unnecessary downtime, is eliminated as electromagnetic interference is avoided and water and dust are prevented from entering the enclosure. This enclosure range is well suited for applications where EMC is required.



IP 54 | TYPE 12 | IK 10

H	600
W	600
D	210
h	570
w	550
d	192
N° of locks	2
Weight (kg)	21.00
Item no.	MASE0606021R5

Material: Body: 1.2 mm zinc plated steel / 1.4 mm MASE0606021R5 and above. Door: 1.2 mm zinc plated steel / 1.4 mm MASE0606021R5 and above / 1.8 mm MASE1006026R5 and above. Mounting plate: 2 mm galvanized steel.

Body: Folded and seam welded. Four 8.5 mm diameter holes for wall fixing, pressed out in 20.4 mm diameter x 2 mm depressions to allow air circulation around the rear part of the enclosure.

Door: Surface mounted with 130° opening. Concealed removable hinges with captive pin. Hinges are mounted for right hand opening only. From size MASE0505021R5 and above there are two removable mounting profiles on the door. Sealing is ensured by a conductive EMC gasket.

Lock: Chrome plated double-bit lock with 3 mm insert and 90° movement. 1000 mm high enclosures and above have espagnolette three point locking system.

Mounting plate: The mounting plate is marked vertically at 10 mm intervals for easy horizontal positioning of equipment. On the top and bottom are holes to facilitate cable fixing. Fixed onto M8 press welded studs to the rear of the enclosure. All sides from 800 mm and above are strengthened by folded edges. By using the AMG accessory the mounting plate can be adjusted to any depth.

Gland Plate Opening: No gland plate opening for a maximum EMI protection.

Earthing: The door is earthed by means of a separate earthing stud M8.

Finish: RAL 7035 structure powder coating on the outside only.

Protection: IP 54 | TYPE 12 | IK 10.

Approvals: CE, GOST, cULus_UL Listed.

Delivery: Zinc plated enclosure body and door, painted on the outside. Door equipped with EMI conductive gasket. Two door mounting profiles from size MASE0505021R5 and above. Earthing facilities.